PRODUCT DATA SHEET

Page: 1 / 2 Revised edition no: 2

Wetrok Karpfrost

Date: 13/4/2006

Supersedes: 2/2/2006

IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade name : Wetrok Karpfrost

Product code : T6

Type of product : detergent

Use : Industrial. For professional use only.

Emergency phone no. : Toxikologisches Informationszentrum: +41 44 251 51 51 (Notfall Tel. 145)

PRODUCT DESCRIPTION

Pictogram

Close product type : Freeeze spray

Product description : For removal of chewing gum and elastomers.

Field of use : For cleaning of temperature resistant surfaces (textile and hard floor coverings) .

Article-No. / sales unit : 10.430 : 180 g aerosol can

10.403 : Wetrok Karpotek (1 x Wetrok Karpfrost, 1 x Wetrok Karpspray, 1x Wetrok

Karpform)

DIRECTIONS FOR USE

Dosage : Undiluted, ready to use.

Use : Spray chewing gum. Allow to work for a short time. Break up chewing gum with

scraper and scrape up. Remove frozen particles immediately (vacuum up). Repeat

procedure as necessary. Also see instructions for Wetrok Karpotek.

Further information : Read product sheet and safety sheet before using. The manufacturer is not liable

for damages arising from misuse.

PRODUCT INFORMATION

Aerosols (75/324/EWG) : Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from

sources of ignition - No smoking. Keep out of the reach of children.

Composition : Regulation 648/2004/EG from 31 March 2004 for detergents.

Waste code (259/93/EWG) : 16 05 04: Gases in pressurised containers (including halons) containing dangerous

substances.

Industrial waste number (ÖNorm

S2100)

: 59803: Pressurised gas containers (spray cans) with residues.

PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Aerosol.

Colour : Colourless.

Odour : Solvent.

pH-value : Not applicable.

Boiling point [°C] : -44
Vapour pressure, 20°C : 23 hPa

Solubility in water : Material is insoluble in water.

Flash point [°C] : -97 Auto-ignition temperature [°C] : 235



PRODUCT DATA SHEET

Page : 2 / 2

Revised edition no : 2

Wetrok Karpfrost

Date: 13/4/2006

Supersedes: 2/2/2006

PHYSICAL AND CHEMICAL PROPERTIES (continued)

Explosion limits - lower [%] : 1.5 Explosion limits - upper [%] : 18.6

REGULATORY INFORMATION

_



Symbol(s) : F+ : Extremely flammable **R-Phrases** : Extremely flammable.

S-phrases : Do not breathe the gas. - If swallowed seek medical advice immediately and show

this container or label. - Use only in well-ventilated areas.

HANDLING AND STORAGE

General : Keep away from sources of ignition - do not smoke.

Technical protective measures : Proper grounding procedures to avoid static electricity should be followed.

Storage : Keep only in the original container in a cool, well ventilated place. Protect from

frost. Keep in fireproof place.

Keep container closed when not in use.

Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50 °C. Do not pierce or burn, even after use.

Storage life : 24

Storage - not in close proximity to : Heat sources.

OTHER INFORMATION

Revision : Changes in the text compared to former version are indicated with *.

WKAFRK001

Prepared by : Alexander Kreuzer

Wetrok Regulatory Affairs

Disclaimer of liability: We have drawn upon sources, which we consider reliable, for the information contained in this document. The correctness of the information is not guaranteed. The conditions or methods of use, storage, handling or disposal of this product are outside our control. For this reason, we assume no responsibility, and expressly deny any liability for loss, damages or expenses that could result from handling, storage, usage or disposal of the product. This document was prepared for this product and may only be used with it.

End of document

