


## Wetrok Imprasol

Date : 8/8/2006  
Supersedes : 9/5/2005

### IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Trade name** : **Wetrok Imprasol**  
**Product code** : G12  
**Type of product** : Surface waterproofing product.  
**Use** : Industrial. For professional use only.  
**Emergency phone no.** : Toxikologisches Informationszentrum: +41 44 251 51 51 (Notfall Tel. 145)

### PRODUCT DESCRIPTION

**Pictogram** 

**Close product type** : **Stone impregnation media**  
**Product description** : For impregnation of natural and artificial stones . Improves the cleanability. To avoid water stains. colourless, transparent .  
**Field of use** : For treatment of porous, very absorbent surfaces ( clay tiles , sandstone , marble , clinker , slate , etc. ) .  
**Article-No. / sales unit** : 17.500 : 10 l canister

### DIRECTIONS FOR USE

**Dosage** : Undiluted, ready to use.  
**Use** : Extremely porous coverings :  
 Clean floor covering thoroughly. The floor must be clean, free from old coatings and dry, before treatment. Apply Wetrok Imprasol with applicator so that the covering is fully moistened. Allow material to soak in. Do not allow to dry out Remove superfluous product. Allow to dry fully.  
 Slightly absorbent coverings :  
 Clean floor covering thoroughly. The floor must be clean, free from old coatings and dry, before treatment. Apply Wetrok Imprasol in sections, by spraying. Work in evenly using the red pad until the surface is free from superfluous substance. Repeat treatment if required, after testing the water.  
**Usage** : 20 - 50 g/m<sup>2</sup>  
**Further information** : Read product sheet and safety sheet before using. The manufacturer is not liable for damages arising from misuse.

### PRODUCT INFORMATION

**WGK class (Germany)** : 1  
**Waste code (259/93/EWG)** : 08 01 11: Waste paint and varnish containing organic solvents or other hazardous substances.  
**Industrial waste number (ÖNorm S2100)** : 55508: Coating material if containing solvents and/or heavy metals and/or biocides as well as not fully hardened residues in containers.  
**UBA-No. (Germany)** : 06100082

### PHYSICAL AND CHEMICAL PROPERTIES

**Physical state at 20 °C** : Liquid.  
**Colour** : Colourless to light yellow.  
**Odour** : Characteristic.  
**pH-value** : Not applicable.  
**Density [g/cm<sup>3</sup>]** : 0.944 - 0.954

## Wetrok Imprasol

Date : 8/8/2006  
Supersedes : 9/5/2005

---

### PHYSICAL AND CHEMICAL PROPERTIES (continued)

---

**Solubility in water** : Material is partially soluble in water.  
**Flash point [°C]** : 73

### REGULATORY INFORMATION

---

**Symbol(s)** : None.  
**S-phrases** : None.  
**Further phrases** : Safety data sheet available for professional user on request.

### HANDLING AND STORAGE

---

**Storage** : Keep only in the original container in a cool, well ventilated place.  
Protect from frost. Keep container closed when not in use.  
**Storage life** : 24  
**GISBAU code** : GH0

### OTHER INFORMATION

---

**Revision** : Changes in the text compared to former version are indicated with \*.  
WIMPRK001  
**Prepared by** : Alexander Kreuzer  
Wetrok Regulatory Affairs

---

Disclaimer of liability: We have drawn upon sources, which we consider reliable, for the information contained in this document. The correctness of the information is not guaranteed. The conditions or methods of use, storage, handling or disposal of this product are outside our control. For this reason, we assume no responsibility, and expressly deny any liability for loss, damages or expenses that could result from handling, storage, usage or disposal of the product. This document was prepared for this product and may only be used with it.

---

End of document