

Wetrok Antiwax

Date : 3/8/2006  
Supersedes : 20/1/2005

IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade name : **Wetrok Antiwax**  
 Product code : B1  
 Type of product : detergent  
 Use : Industrial. For professional use only.  
 Emergency phone no. : Toxikologisches Informationszentrum: +41 44 251 51 51 (Notfall Tel. 145)

PRODUCT DESCRIPTION

Pictogram



Close product type : **Universal cleaner**  
 Product description : Very high performance cleaner. For removal of oil, fat and general industrial soiling . Also suitable for removing wax coatings (protective films) . Slightly foaming. Slightly alkaline. Non-perfumed.  
 Field of use : For cleaning of washable, alkaline-resistant surfaces / floor coverings ( PVC , natural and artificial stones , clinker , rubber , etc. ) . Restrictedly suitable for linoleum . Wetrok Relino or Wetrok Antiwax forte should be used for cleaning linoleum and alkaline sensitive surfaces.  
 Article-No. / sales unit : 11.100 : 10 l canister  
 11.105 : 200 l barrel  
 10.202 : 10 x 500 ml dispenser

DIRECTIONS FOR USE

Dosage : Adjust dosage according to degree of soiling. The proper dosage saves costs and protects the environment.  
 Conversion 1 % corresponds to approx. 1 dl / 10 l = 100 ml / 10 l = 0.1 l / 10 l.

	Wash (mop)	Scrub-extraction	Burnisher
Maintenance cleaning	0.5 - 1 %	0.5 - 1 %	--
Interval cleaning	2 - 5 %	2 - 5 %	2 - 5 %
Basic cleaning	--	--	10 - 30 %

Use : wash (mop) :  
 Soak mop with Wetrok Antiwax solution, press out well. Clean floor coverings thoroughly.  
 scrub-extraction :  
 Fill fresh water tank with Wetrok Antiwax solution. Attach a suitable pad / brush. Clean floor coverings thoroughly.  
 Basic cleaning :  
 Wash floors, taking up dust (wipe damp). Spread Wetrok Antiwax solution evenly over the floor covering. Allow to work for approx. 10 - 15 minutes. Do not allow to dry out Scrub mechanically (add water where necessary) and allow to work in again for 10 - 15 minutes. Do not allow to dry out Vacuum up loosened coating material / dirt. Rinse thoroughly with clear water and vacuum up (until rinsing water is pH-neutral). The procedure should be repeated with a higher concentration, if the coating can not be removed fully.  
 Wipe damp (by hand) :  
 Moisten cloth or sponge with Wetrok Antiwax solution, wring out well. Clean surface thoroughly. Wipe dry where necessary.

Further information : Use a dosage of max. 5 % on linoleum. Rinse afterwards with water when using dosages above 10 %. Read product sheet and safety sheet before using. The manufacturer is not liable for damages arising from misuse.

**Wetrok Antiwax**

Date : 3/8/2006  
Supersedes : 20/1/2005

**PRODUCT INFORMATION**


**Composition** : Regulation 648/2004/EG from 31 March 2004 for detergents.  
**- Ingredients** : < 5% : - aromatic hydrocarbons - soap  
 5% - 15% : - non-ionic surfactants  
**WGK class (Germany)** : 1  
**Waste code (259/93/EWG)** : 20 01 29: detergents containing hazardous substances.  
**Industrial waste number (ÖNorm S2100)** : 59402: Tensides and preparations containing tensides as well residues of washing and cleaning substances.

**PHYSICAL AND CHEMICAL PROPERTIES**

**Physical state at 20 °C** : Liquid.  
**Colour** : Colourless.  
**Odour** : Characteristic.  
**pH-value** : 9.5 - 10.5  
**Density [g/cm<sup>3</sup>]** : 1.026 - 1.036  
**Solubility in water** : The material disperses in water.  
**Flash point [°C]** : Not applicable.

**REGULATORY INFORMATION**

-



**Symbol(s)** : Xi : Irritant  
**R-Phrases** : Irritating to respiratory system and skin. - Risk of serious damage to eyes.  
**S-phrases** : Keep out of the reach of children. - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. - Wear eye/face protection. - If swallowed seek medical advice immediately and show this container or label.

**HANDLING AND STORAGE**

**Storage** : Keep only in the original container in a cool, well ventilated place. Protect from frost. Keep container closed when not in use.  
**Storage life** : 24  
**GISBAU code** : GG60

**OTHER INFORMATION**

**Revision** : Changes in the text compared to former version are indicated with \*.  
 WANTIK003  
**Prepared by** : Alexander Kreuzer  
 Wetrok Regulatory Affairs

Disclaimer of liability: We have drawn upon sources, which we consider reliable, for the information contained in this document. The correctness of the information is not guaranteed. The conditions or methods of use, storage, handling or disposal of this product are outside our control. For this reason, we assume no responsibility, and expressly deny any liability for loss, damages or expenses that could result from handling, storage, usage or disposal of the product. This document was prepared for this product and may only be used with it.

**Wetrok Antiwax**

Date : 3/8/2006  
Supersedes : 20/1/2005

---

**End of document**