

Wetrok Antiwax forte

Date : 25/4/2006
Supersedes : 21/10/2005

IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Trade name : **Wetrok Antiwax forte**
 Product code : B2
 Type of product : detergent
 Use : Industrial. For professional use only.
 Emergency phone no. : Toxikologisches Informationszentrum: +41 44 251 51 51 (Notfall Tel. 145)

PRODUCT DESCRIPTION

Pictogram



Close product type : **Basic and industry cleaner**
 Product description : Very high performance cleaner. For removal of oil, fat and general industrial soiling . Slightly foaming. Containing solvents. Slightly alkaline. Also suitable for removing polymer and wax coatings (protective films) .
 Field of use : For cleaning of washable, solvent resistant surfaces / floor coverings (PVC , natural and artificial stones , clinker , etc.) . Also suitable for the cleaning of unsealed wooden floors and for the deep cleaning of linoleum. Not suitable for Regular cleaning of floor coverings treated with self-shining dispersions.
 Article-No. / sales unit : 11.000 : 10 l canister
 11.005 : 200 l barrel
 10.201 : 10 x 500 ml dispenser

DIRECTIONS FOR USE

Dosage : Adjust dosage according to degree of soiling. The proper dosage saves costs and protects the environment.
 Conversion 1 % corresponds to approx. 1 dl / 10 l = 100 ml / 10 l = 0.1 l / 10 l.

	Wash (mop)	Scrub-extraction	Burnisher
Maintenance cleaning	0.5 - 1 %	0.5 - 1 %	--
Interval cleaning	2 - 5 %	2 - 5 %	2 - 5 %
Basic cleaning	--	--	30 - 100 %

Use : wash (mop) :
 Soak mop with Wetrok Antiwax forte solution, press out well. Clean floor coverings thoroughly.
 scrub-extraction :
 Fill fresh water tank with Wetrok Antiwax forte solution. Attach a suitable pad / brush. Clean floor coverings thoroughly.
 Basic cleaning :
 Wash floors, taking up dust (wipe damp). Spread Wetrok Antiwax forte solution evenly over the floor covering. Allow to work for approx. 10 - 15 minutes. Do not allow to dry out Scrub mechanically (add water where necessary) and allow to work in again for 10 - 15 minutes. Do not allow to dry out Vacuum up loosened coating material / dirt. Rinse thoroughly with clear water and vacuum up (until rinsing water is pH-neutral). The procedure should be repeated with a higher concentration, if the coating can not be removed fully.
 Wipe damp (by hand) :
 Moisten cloth or sponge with Wetrok Antiwax forte solution, wring out well. Clean surface thoroughly. Wipe dry where necessary.

Further information : Use max. 5 % Wetrok Antiwax forte on painted surfaces or elastomers (rubber, natural rubber). Read product sheet and safety sheet before using. The manufacturer is not liable for damages arising from misuse.

Wetrok Antiwax forte

Date : 25/4/2006
Supersedes : 21/10/2005

PRODUCT INFORMATION

Composition : Regulation 648/2004/EG from 31 March 2004 for detergents.
- Ingredients : < 5% : - phosphates - non-ionic surfactants - soap
- Allergenic perfume ingredients : Limonen.
WGK class (Germany) : 2
Waste code (259/93/EWG) : 20 01 29: detergents containing hazardous substances.
Industrial waste number (ÖNorm S2100) : 59405: Washing and cleaning wastes if they are labelled as flammable, corrosive, environmentally hazardous or damaging to health (less poisonous).

PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Liquid.
Colour : Colourless to light yellow.
Odour : Characteristic.
pH-value : 8.6 - 9.6
Density [g/cm³] : 1.045-1.055
Solubility in water : The material disperses in water.
Flash point [°C] : Not applicable.

REGULATORY INFORMATION

-




Symbol(s) : Xi : Irritant
N : Dangerous for the environment

R-Phrases : May cause sensitization by skin contact. - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases : Keep out of the reach of children. - Wear suitable gloves. - If swallowed seek medical advice immediately and show this container or label. - Avoid release to the environment. Refer to special instructions/Safety data sheets.

HANDLING AND STORAGE

Storage : Keep only in the original container in a cool, well ventilated place. Protect from frost. Keep container closed when not in use.
Storage life : 24
GISBAU code : GG20

OTHER INFORMATION

Revision : Changes in the text compared to former version are indicated with *.
WAWFOK002
Prepared by : Alexander Kreuzer
Wetrok Regulatory Affairs

Disclaimer of liability: We have drawn upon sources, which we consider reliable, for the information contained in this document. The correctness of the information is not guaranteed. The conditions or methods of use, storage, handling or disposal of this product are outside our control. For this reason, we assume no responsibility, and expressly deny any liability for loss, damages or

Wetrok Antiwax forte

Date : 25/4/2006
Supersedes : 21/10/2005

expenses that could result from handling, storage, usage or disposal of the product. This document was prepared for this product and may only be used with it.

End of document