

**Wetrok Rewit 2000**

Date : 15/8/2006  
Supersedes : 7/2/2005

**IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Trade name** : **Wetrok Rewit 2000**  
**Product code** : B7  
**Type of product** : detergent  
**Use** : Industrial. For professional use only.  
**Emergency phone no.** : Toxikologisches Informationszentrum: +41 44 251 51 51 (Notfall Tel. 145)

**PRODUCT DESCRIPTION**

**Pictogram**



**Close product type** : **Basic and industry cleaner**  
**Product description** : For removal of oil, fat and general industrial soiling . Also suitable for removing polymer and wax coatings (protective films) . Slightly foaming. Containing solvents. Slightly alkaline. Slightly perfumed.  
**Field of use** : For cleaning of washable, alkaline-resistant floor coverings ( PVC , natural and artificial stones , clinker , etc. ) . Also suitable for the cleaning of asphalt . Not suitable for linoleum , rubber . Not suitable for Regular cleaning of floor coverings treated with self-shining dispersions.  
**Article-No. / sales unit** : 11.200 : 10 l canister  
 11.205 : 200 l barrel

**DIRECTIONS FOR USE**

**Dosage** : Adjust dosage according to degree of soiling. The proper dosage saves costs and protects the environment.  
 Conversion 1 % corresponds to approx. 1 dl / 10 l = 100 ml / 10 l = 0.1 l / 10 l.

	Wash (mop)	Scrub-extraction	Burnisher
Maintenance cleaning	0.5 - 1 %	0.5 - 1 %	--
Interval cleaning	2 - 5 %	2 - 5 %	2 - 5 %
Basic cleaning	--	--	10 - 20 %

**Use** : wash (mop) :  
 Soak mop with Wetrok Rewit 2000 solution, press out well. Clean floor coverings thoroughly.  
 scrub-extraction :  
 Fill fresh water tank with Wetrok Rewit 2000 solution. Attach a suitable pad / brush. Clean floor coverings thoroughly.  
 Basic cleaning :  
 Wash floors, taking up dust (wipe damp). Spread Wetrok Rewit 2000 solution evenly over the floor covering. Allow to work for approx. 10 - 15 minutes. Do not allow to dry out Scrub mechanically (add water where necessary) and allow to work in again for 10 - 15 minutes. Do not allow to dry out Vacuum up loosened coating material / dirt. Rinse thoroughly with clear water and vacuum up (until rinsing water is pH-neutral). The procedure should be repeated with a higher concentration, if the coating can not be removed fully.

**Further information** : Use a dosage of max. 5 % on linoleum. Read product sheet and safety sheet before using. The manufacturer is not liable for damages arising from misuse.

**Wetrok Rewit 2000**

Date : 15/8/2006  
Supersedes : 7/2/2005

**PRODUCT INFORMATION**

**Composition** : Regulation 648/2004/EG from 31 March 2004 for detergents.  
**- Ingredients** : < 5% : - NTA (Nitrilotriacetic acid) and salts thereof  
 5% - 15% : - non-ionic surfactants  
**- Allergenic perfume ingredients** : Limonen.  
**WGK class (Germany)** : 1  
**Waste code (259/93/EWG)** : 20 01 29: detergents containing hazardous substances.  
**Industrial waste number (ÖNorm S2100)** : 59405: Washing and cleaning wastes if they are labelled as flammable, corrosive, environmentally hazardous or damaging to health (less poisonous).

**PHYSICAL AND CHEMICAL PROPERTIES**

**Physical state at 20 °C** : Liquid.  
**Colour** : Slightly yellow.  
**Odour** : Characteristic.  
**pH-value** : 10.6 - 11.6  
**Acid/alkali reserve [g NaOH/100g]** : 1.1  
**Density [g/cm3]** : 1.001-1.011  
**Solubility in water** : The material disperses in water.  
**Flash point [°C]** : Not applicable.

**REGULATORY INFORMATION**

-



**Symbol(s)** : Xi : Irritant  
**R-Phrases** : Irritating to skin. - Risk of serious damage to eyes. - May cause sensitization by skin contact. - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
**S-phrases** : Keep out of the reach of children. - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. - Wear suitable gloves and eye/face protection. - If swallowed seek medical advice immediately and show this container or label.

**HANDLING AND STORAGE**

**Storage** : Keep only in the original container in a cool, well ventilated place. Protect from frost. Keep container closed when not in use.  
**Storage life** : 24  
**GISBAU code** : GG60

**OTHER INFORMATION**

**Revision** : Changes in the text compared to former version are indicated with \*.  
 WRW2KK001  
**Prepared by** : Alexander Kreuzer  
 Wetrok Regulatory Affairs

## Wetrok Rewit 2000

Date : 15/8/2006  
Supersedes : 7/2/2005

---

Disclaimer of liability: We have drawn upon sources, which we consider reliable, for the information contained in this document. The correctness of the information is not guaranteed. The conditions or methods of use, storage, handling or disposal of this product are outside our control. For this reason, we assume no responsibility, and expressly deny any liability for loss, damages or expenses that could result from handling, storage, usage or disposal of the product. This document was prepared for this product and may only be used with it.

---

**End of document**